


Light Shadow Fixed No Trim Dali Version 12 Spots Optic Spot

03.8881.40ADA - White/Black

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2773 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 32.4W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 10 |
| Beam angle C90-270 (°) | 10 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 10° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 50052 | 0.18 | |
| 2 | 12513 | 0.36 | |
| 3 | 5561 | 0.54 | |
| 4 | 3128 | 0.72 | |
| 5 | 2002 | 0.90 | |

Luminous flux luminaire
2773 lm (EXTREME CUT OFF)

Electrical


| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical


| | |
|----------------------------|-------------|
| Color | White/Black |
| Orientation | Fixed |
| Recessed depth (mm) | 75 |
| Weight (kg) | 0.66 |
| Length (mm) | 420 |

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Fixed No Trim Dali Version 12 Spots Optic Spot



Pre-installation Frame
08.0513.00

Accessory for mounting of No Trim
continuous line.
08.0052.90