



03.9203.14ADA - Black/Gold

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).



Number of heads LED Lamp category Power (W) 5.4W CCT (K) 2700K CRI


445 Net lumen (lm)

Mountings Ceiling recessed Environment Indoor dry location

90

Optical

Lighting type LED type Direct Power LED Light distribution Symmetric Optical type Medium Beam angle (°) 22 Beam angle C90-270 (°) 22




Luminous flux luminaire 445 lm (EXTREME CUT OFF)

Without

Emergency

Insulation class

Beam Angle:		22°
h(m)	E(lx)	D(m)
1	2976	0.39
2	744	0.78
3	331	1.17
4	186	1.56
5	119	1.95





Electrical

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable Yes

Remote included Driver Driver type Dimmable DALI

Physical

Color Black/Gold Orientation Fixed Recessed depth (mm) 150 Weight (kg) 0.25 Length (mm) 70

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 2 Spots Optic Medium





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0510.00