


## Light Shadow Fixed No Trim Dali Version 2 Spots Optic Medium

03.9203.40ADA - White/Gold

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	445
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	5.4W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	22
<b>Beam angle C90-270 (°)</b>	22



Beam Angle:	22°
	h(m) E(lx) D(m)
	1 2976 0.39
	2 744 0.78
	3 331 1.17
	4 186 1.56
	5 119 1.95

Luminous flux luminaire  
445 lm (EXTREME CUT OFF)



### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	White/Gold
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	150
<b>Weight (kg)</b>	0.25
<b>Length (mm)</b>	70

### Note

It requires a pre-installation frame, to be ordered separately.



## Light Shadow Fixed No Trim Dali Version 2 Spots Optic Medium



---

Pre-installation Frame  
08.0510.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90