



# Light Shadow Fixed No Trim Dali Version 2 Spots Optic Medium

#### 03.9212.14ADA - Black/Chrome


Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).

# Main specifications

Number of heads	1	Net lumen (lm)	475
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

# Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Ream angle C90-270 (°)	22



30 7	3190 Ca T	3U ,
Lumino	ous flux lumi	naire
475 lm	(EXTREME CU	T OFF)

Bear	Beam Angle:	
h(m)	E( <b>l</b> x)	D(m)
1	3196	0.39
2	799	0.77
3	355	1.16
4	200	1.55
5	128	1.94

#### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Dimmable DALI

# Physical

Driver type

Color	Black/Chrome
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim Dali Version 2 Spots Optic Medium





Pre-installation Frame 08.0510.00

Accessory for mounting of No Trim continuous line. 08.0052.90