




03.8852.14ADA - Black/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).





R		1	





11/	าวเก	specifications
10	ıaııı	SUCCINCATIONS


Number of heads LED Lamp category Power (W) 5.4W CCT (K) 2700K CRI 90

Net lumen (lm) Mountings Environment

453 Ceiling recessed Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10



Luminous flux luminaire 453 lm (EXTREME CUT OFF)

Beam Angle: 10° E(lx) h(m) D(m) 8285 0.17 2 2071 0.35 3 0.52 921 4 518 0.70

331

0.87

5

Without

П

**Electrical** 

Frequency (Hz) 50/60 **Emergency** Voltage (V) 220.00 Insulation class Dimmable Yes

Driver Remote included Driver type Dimmable DALI 1

Physical

Color Black/White Orientation Fixed Recessed depth (mm) 150 Weight (kg) 0.25 Length (mm) 70

## Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Fixed No Trim Dali Version 2 Spots Optic Spot





Pre-installation Frame 08.0510.00

Accessory for mounting of No Trim continuous line. 08.0052.90