

Light Shadow Fixed No Trim Dali Version 2 Spots Optic Spot

03.8856.40ADA - White/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 475 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 5.4W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 10 |
| Beam angle C90-270 (°) | 10 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 10° | | |
| | h(m) | E(lx) | D(m) |
| | 1 | 8680 | 0.17 |
| | 2 | 2170 | 0.35 |
| | 3 | 964 | 0.52 |
| | 4 | 542 | 0.70 |
| | 5 | 347 | 0.87 |

Luminous flux luminaire
475 lm (EXTREME CUT OFF)

Electrical


| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | |
|----------------------------|-------------|
| Color | White/White |
| Orientation | Fixed |
| Recessed depth (mm) | 150 |
| Weight (kg) | 0.25 |
| Length (mm) | 70 |

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Fixed No Trim Dali Version 2 Spots Optic Spot



Accessory for mounting of No Trim
continuous line.
08.0052.90