


## Light Shadow Fixed No Trim Dali Version 2 Spots Optic Wide Flood

03.8352.14ADA - Black/Chrome

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

Number of heads	1	Net lumen (lm)	446
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	44
Beam angle C90-270 (°)	44



Beam Angle: 44°

h(m)	E(lx)	D(m)
1	929	0.80
2	232	1.60
3	103	2.40
4	58	3.19
5	37	3.99

Luminous flux luminaire  
446 lm (EXTREME CUT OFF)

### Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable DALI		

### Physical


Color	Black/Chrome
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

### Note

It requires a pre-installation frame, to be ordered separately.



## Light Shadow Fixed No Trim Dali Version 2 Spots Optic Wide Flood



---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90

---

Pre-installation Frame  
08.0510.00