

# Light Shadow Fixed No Trim Dali Version 4 Spots Optic Medium

### 03.9232.14ADA - Black/Chrome


Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

# Main specifications

Number of neads	I	ivet lumen (im)	802
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry locatio
CCT (K)	3000K		
CRI	90		

# Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Lumino	us flux	lumir	naire
802 lm	(EXTREI	ME CUT	OFF)

Bea	Beam Angle:	
h(m)	) E(lx)	D(m)
1	5397	0.39
2	1349	0.77
3	600	1.16
4	337	1.55
5	216	1 94

#### **Electrical**

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Dimmable DALI

# Physical

Driver type

Color	Black/Chrom
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim Dali Version 4 Spots Optic Medium





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90