



Light Shadow Fixed No Trim Dali Version 4 Spots Optic Medium

03.9232.14ADA - Black/Chrome


Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

Main specifications

Number of neads	I	ivet iumen (im)	802
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



K /			4	
30°	5397 cd	30°	5	
Luminous flux luminaire				
802 lm	(EXTREME CU	ΓOFF)		

Beam Angle:		22°
h(m)	E(l ×)	D(m
1	5397	0.39
2	1349	0.77
3	600	1.16
4	337	1.55
5	216	1.94

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Dimmable DALI

Physical

Driver type

Color	Black/Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 4 Spots Optic Medium





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0511.00