




03.8861.14ADA - Black/Black

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).











Main specifications
Number of heads

vulliber of fleads	
amp category	LED
Power (W)	10.8W
CCT (K)	2700K
CRI	90


Net lumen (lm) Mountings Environment

724

Ceiling recessed Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire 724 lm (EXTREME CUT OFF)

Beam Angle:		10°
h(n	n) E(l x)	D(m)
1	13076	0.18
2	3269	0.36
3	1453	0.54
4	817	0.72

523

0.90

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		

Driver Remote included Driver type Dimmable DALI

Physical

Color	Black/Black
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 4 Spots Optic Spot





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90