




03.8866.14ADA - Black/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).












Number of neads	1
Lamp category	LED
Power (W)	10.8W
CCT (K)	3000K
CRI	90

Net lumen (lm) Mountings Environment 805 Ceiling recessed Indoor dry location

Optical

Lighting type	Direct
ED type	Power LED
ight distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire 805 lm (EXTREME CUT OFF)

Bea	am Angle:	10°
h(n	n) E(lx)	D(m
1	14176	0.18
2	3544	0.36
3	1575	0.55
4	886	0.73
5	547	∩ Q1

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		

Driver type Remote included
Driver type Dimmable DALI
1

Physical

Color	Black/Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 4 Spots Optic Spot





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90