


## Light Shadow Fixed No Trim Dali Version 4 Spots Optic Wide Flood

■ 03.8359.40ADA - White/Black

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

Number of heads	1	Net lumen (lm)	735
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle: 46°

h(m)	E(lx)	D(m)
1	1395	0.84
2	349	1.69
3	155	2.53
4	87	3.38
5	56	4.22

Luminous flux luminaire  
735 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

### Physical


Color	White/Black
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

### Note

It requires a pre-installation frame, to be ordered separately.



# Light Shadow Fixed No Trim Dali Version 4 Spots Optic Wide Flood



Pre-installation Frame  
08.0511.00

Accessory for mounting of No Trim  
continuous line.  
08.0052.90