


Light Shadow Fixed No Trim Dali Version 4 Spots Optic Wide Flood

03.8364.40ADA - White/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 789 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 10.8W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|------------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 44 |
| Beam angle C90-270 (°) | 44 |



Beam Angle: 44°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1644 | 0.80 |
| 2 | 411 | 1.60 |
| 3 | 183 | 2.40 |
| 4 | 103 | 3.19 |
| 5 | 66 | 3.99 |

Luminous flux luminaire
789 lm (EXTREME CUT OFF)

Electrical

| | | | |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical


| | |
|---------------------|--------------|
| Color | White/Chrome |
| Orientation | Fixed |
| Recessed depth (mm) | 75 |
| Weight (kg) | 0.34 |
| Length (mm) | 140 |

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Fixed No Trim Dali Version 4 Spots Optic Wide Flood



Accessory for mounting of No Trim
continuous line.
08.0052.90

Pre-installation Frame
08.0511.00