



Light Shadow Fixed No Trim Dali Version 8 Spots Optic Flood

03.9258.40ADA - White/Gold

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	1850
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	5691	0.60
2	1423	1.20
3	632	1.79
4	356	2.39
5	228	2.99

Luminous flux luminaire
1850 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		


Physical

Color	White/Gold
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 8 Spots Optic Flood



Accessory for mounting of No Trim
continuous line.
08.0052.90

Pre-installation Frame
08.0512.00