

## Light Shadow Fixed No Trim Dali Version 8 Spots Optic Medium

03.9253.14ADA - Black/Gold

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1866                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 21.6W | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |


### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Medium    |
| <b>Beam angle (°)</b>         | 22        |
| <b>Beam angle C90-270 (°)</b> | 22        |



|             |                 |
|-------------|-----------------|
| Beam Angle: | 22°             |
|             | h(m) E(lx) D(m) |
| 1           | 12472 0.39      |
| 2           | 3118 0.78       |
| 3           | 1386 1.17       |
| 4           | 779 1.56        |
| 5           | 499 1.95        |

Luminous flux luminaire  
1866 lm (EXTREME CUT OFF)



### Electrical


|                       |                 |                         |         |
|-----------------------|-----------------|-------------------------|---------|
| <b>Frequency (Hz)</b> | 50/60           | <b>Emergency</b>        | Without |
| <b>Voltage (V)</b>    | 220.00          | <b>Insulation class</b> | II      |
| <b>Dimmable</b>       | Yes             |                         |         |
| <b>Driver</b>         | Remote included |                         |         |
| <b>Driver type</b>    | Dimmable DALI   |                         |         |
|                       | 1               |                         |         |

### Physical

|                            |            |
|----------------------------|------------|
| <b>Color</b>               | Black/Gold |
| <b>Orientation</b>         | Fixed      |
| <b>Recessed depth (mm)</b> | 75         |
| <b>Weight (kg)</b>         | 0.50       |
| <b>Length (mm)</b>         | 280        |

### Note

It requires a pre-installation frame, to be ordered separately.



## Light Shadow Fixed No Trim Dali Version 8 Spots Optic Medium



---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90