mmm

51x296

55 EAL CE RETILAP

∰ 🖓

GWT 850°

## Light Shadow Fixed No Trim Dali Version 8 Spots Optic Spot

03.8870.40ADA - White/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 21.6W 2700K 90	Net lumen (lm) Mountings Environment	1819 Ceiling recessed Indoor dry location	
Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Power LED Symmetric Spot 10 10	90° 60° 30° 32048 cc Luminous flux I 1819 lm (EXTREM	uminaire	Beam Angle: 10   h(m) E(lx) D(r   1 32048 0.1   2 8012 0.3   3 3561 0.5   4 2003 0.7   5 1282 0.9
Electrical Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50/60 220.00 Yes Remote included Dimmable DALI 1	Emergency Insulation class	Without II	
Physical Color Orientation Recessed depth (mm) Weight (kg) Length (mm)	White/Chrome Fixed 75 0.50 280			

## Note

It requires a pre-installation frame, to be ordered separately.

 $https://www.flos.com/professional-space/architectural/products/light-shadow-fixed-no-trim-dali-version-8-spots-optic-spot-\dots fixed-no-trim-dali-version-8-spots-optic-spot-8-spots-optic-spot-8-spots-optic-8-spots-optic-8-spots-optic-8-spots-optic-8-spots-optic-8-spots-optic-8-spots-optic-8-spots-optic-8-spots-optic-8-spots-0$ 

## Light Shadow Fixed No Trim Dali Version 8 Spots Optic Spot





Pre-installation Frame 08.0512.00

Accessory for mounting of No Trim continuous line. 08.0052.90