







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).












Number of heads	1
amp category	LED
Power (W)	21.6W
CCT (K)	3000K
CRI	90

Net lumen (lm) Mountings Environment 1859

Ceiling recessed Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire 1859 lm (EXTREME CUT OFF)

Beam Angle:		10°
h(n	n) E(l x)	D(m)
1_	32900	0.18
2	8225	0.36
3	3656	0.55
4	2056	0.73
	2030	0.73

1316 0.91

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		

Remote included

Dimmable DALI

Physical

Driver type

Driver

Color	White/Gold
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 8 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0512.00