
location









Light Shadow Fixed No Trim Dali Version 8 Spots Optic Wide Flood

03.8370.40ADA - White/White


Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Main specifications

Number of heads	1	Net lumen (lm)	1847
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Lumino	us flux	luminaire
1847 lm	(EXTREM	ME CUT OFF

Bea	Beam Angle:	
h(m)	E(lx)	D(m)
1	3443	0.83
2	861	1.67
3	383	2.50
4	215	3.34
5	138	<u>4</u> 17

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Dimmable DALI

Physical

Driver type

Color	White/Whit
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 8 Spots Optic Wide Flood





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0512.00