2610

Ceiling recessed

Indoor dry location








Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).











Main sp	ecifications
---------	--------------

Number of heads	1	
Lamp category	LED	
Power (W)	32.4W	
CCT (K)	2700K	
CRI	90	

## Net lumen (lm) Mountings Environment

Direct

Flood

33

33

Power LED

Symmetric

90°	90°-
60°	60°.
30° 8160 cd	30°

Lumino	us flux	luminaire
2610 lm	(EXTREN	IE CUT OFF)

Beam Angle: 33°

h(m) = E(Ix)D(m) 8160 0.60 2 2040 1.19 3 907 1.79

4 510 2.39 5 326 2.99

## **Electrical**

Optical Lighting type

LED type

Optical type

Beam angle (°)

Light distribution

Beam angle C90-270 (°)

Frequency (Hz)	50/60	Insulation class	П
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		

Without

## **Emergency Physical**

•			
Color	Black/Black	Length (mm)	427
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.66		

## Note

Pre-installation frame not required.