



### Light Shadow Fixed Trim 2 Spots Optic Flood

03.9118.14A - Black/Gold

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




#### Main specifications

Number of heads	1	Net lumen (lm)	462
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

#### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	1423	0.60
2	356	1.20
3	158	1.79
4	89	2.39
5	57	2.99

Luminous flux luminaire  
462 lm (EXTREME CUT OFF)

#### Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

#### Physical

Color	Black/Gold	Length (mm)	77
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	150		
Weight (kg)	0.25		

#### Note

Pre-installation frame not required.

