



Light Shadow Fixed Trim 2 Spots Optic Spot

03.8826.14A - Black/Chrome

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 477 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 5.4W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 10 |
| Beam angle C90-270 (°) | 10 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 10° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 8394 | 0.18 | |
| 2 | 2098 | 0.36 | |
| 3 | 933 | 0.55 | |
| 4 | 525 | 0.73 | |
| 5 | 336 | 0.91 | |

Luminous flux luminaire
477 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Voltage (V) | 220.00 | | |
| Dimmable | No | | |
| Driver | Remote included | | |
| Emergency | Without | | |

Physical

| | | | |
|----------------------------|--------------|--------------------|----|
| Color | Black/Chrome | Length (mm) | 77 |
| Orientation | Fixed | | |
| Trim | yes | | |
| Recessed depth (mm) | 150 | | |
| Weight (kg) | 0.25 | | |

Note

Pre-installation frame not required.