


Light Shadow Fixed Trim 2 Spots Optic Wide Flood

■ ■ 03.8305.14A - Black/Black

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	464
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle:	46°		
h(m)	E(lx)	D(m)	
1	881	0.84	
2	220	1.69	
3	98	2.53	
4	55	3.38	
5	35	4.22	

Luminous flux luminaire
464 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

Physical

Color	Black/Black	Length (mm)	77
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	150		
Weight (kg)	0.25		

Note

Pre-installation frame not required.

