



Light Shadow Fixed Trim Dali Version 12 Spots Optic Flood

03.9178.40ADA - White/Gold

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	2655
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33




Beam Angle: 33°		
h(m)	E(lx)	D(m)
1	8170	0.60
2	2042	1.20
3	908	1.79
4	511	2.39
5	327	2.99

Luminous flux luminaire
2655 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable push, Electronic dimmable DALI		

Certification / Marking



Physical

Color	White/Gold	Length (mm)	427
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.66		

Note

Pre-installation frame not required.