


## Light Shadow Fixed Trim Dali Version 2 Spots Optic Flood

03.9116.14ADA - Black/Black

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	455
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	5.4W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	33
<b>Beam angle C90-270 (°)</b>	33



<b>Beam Angle:</b>	33°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	1421	0.60	
2	355	1.19	
3	158	1.79	
4	89	2.39	
5	57	2.99	

Luminous flux luminaire  
455 lm (EXTREME CUT OFF)


### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable DALI		

### Physical

<b>Color</b>	Black/Black	<b>Length (mm)</b>	77
<b>Orientation</b>	Fixed		
<b>Trim</b>	yes		
<b>Recessed depth (mm)</b>	150		
<b>Weight (kg)</b>	0.25		

### Certification / Marking



### Note

Pre-installation frame not required.