Light Shadow Fixed Trim Dali Version 2 Spots Optic Medium 03.9112.14ADA - Black/Chrome

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).


| Main specifications Number of heads Lamp category Power (W) CCT (K) CRI | 1 LED 5.4W 3000K 90 | Net lumen (lm) Mountings Environment | 475 Ceiling recessed Indoor dry location | | |
|--|---|--|--|---|---|
| Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) | Direct Power LED Symmetric Medium 22 22 | 90° 60° 30° 3196 cc Luminous flux 475 lm (EXTREM | | Beam Angle: h(m) E(lx) 1 3196 2 799 3 355 4 200 5 128 | 22° D(m) 0.39 0.77 1.16 1.55 1.94 |
| Electrical Frequency (Hz) Voltage (V) Dimmable Driver Driver type | 50/60 220.00 Yes Remote included Dimmable DALI 1 | Emergency Insulation class | Without II | | |
| Physical Color Orientation Trim Recessed depth (mm) Weight (kg) | Black/Chrome Fixed yes 150 0.25 | Length (mm) | 77 | | |

Note

Pre-installation frame not required.

Main spe Number of





| K 03 | V | IP 55 | EAL | CE | RETILAP |
|-------------|---|----------|-----|----|---------|
| GWT 850° | | | | | |