


## Light Shadow Fixed Trim Dali Version 2 Spots Optic Wide Flood

03.8303.40ADA - White/Gold

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 432                 |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 5.4W  | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 2700K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |            |
|-------------------------------|------------|
| <b>Lighting type</b>          | Direct     |
| <b>LED type</b>               | Power LED  |
| <b>Light distribution</b>     | Symmetric  |
| <b>Optical type</b>           | Wide flood |
| <b>Beam angle (°)</b>         | 46         |
| <b>Beam angle C90-270 (°)</b> | 46         |



|                    |             |              |             |
|--------------------|-------------|--------------|-------------|
| <b>Beam Angle:</b> | 46°         |              |             |
|                    | <b>h(m)</b> | <b>E(lx)</b> | <b>D(m)</b> |
|                    | 1           | 795          | 0.84        |
|                    | 2           | 199          | 1.69        |
|                    | 3           | 88           | 2.53        |
|                    | 4           | 50           | 3.38        |
|                    | 5           | 32           | 4.22        |

Luminous flux luminaire  
432 lm (EXTREME CUT OFF)

### Electrical

|                       |                 |                         |         |
|-----------------------|-----------------|-------------------------|---------|
| <b>Frequency (Hz)</b> | 50/60           | <b>Emergency</b>        | Without |
| <b>Voltage (V)</b>    | 220.00          | <b>Insulation class</b> | II      |
| <b>Dimmable</b>       | Yes             |                         |         |
| <b>Driver</b>         | Remote included |                         |         |
| <b>Driver type</b>    | Dimmable DALI   |                         |         |
|                       | 1               |                         |         |

### Physical

|                            |            |                    |    |
|----------------------------|------------|--------------------|----|
| <b>Color</b>               | White/Gold | <b>Length (mm)</b> | 77 |
| <b>Orientation</b>         | Fixed      |                    |    |
| <b>Trim</b>                | yes        |                    |    |
| <b>Recessed depth (mm)</b> | 150        |                    |    |
| <b>Weight (kg)</b>         | 0.25       |                    |    |

### Note

Pre-installation frame not required.

