

## Light Shadow Fixed Trim Dali Version 4 Spots Optic Flood

03.9137.40ADA - White/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	803
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	10.8W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	33
<b>Beam angle C90-270 (°)</b>	33



<b>Beam Angle:</b>	33°	
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	2485	0.60
2	621	1.19
3	276	1.79
4	155	2.38
5	99	2.98

Luminous flux luminaire  
803 lm (EXTREME CUT OFF)




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	White/Chrome	<b>Length (mm)</b>	147
<b>Orientation</b>	Fixed		
<b>Trim</b>	yes		
<b>Recessed depth (mm)</b>	75		
<b>Weight (kg)</b>	0.34		



### Note

Pre-installation frame not required.