


Light Shadow Fixed Trim Dali Version 4 Spots Optic Spot

03.8834.14ADA - Black/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	805
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle:	10°		
	h(m)	E(lx)	D(m)
1	14176	0.18	
2	3544	0.36	
3	1575	0.55	
4	886	0.73	
5	567	0.91	

Luminous flux luminaire
805 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

Physical

Color	Black/Chrome	Length (mm)	147
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.34		

Note

Pre-installation frame not required.

