


Light Shadow Fixed Trim Dali Version 4 Spots Optic Wide Flood

03.8315.14ADA - Black/Gold

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	764
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle:	46°		
	h(m)	E(lx)	D(m)
1	1407	0.84	
2	352	1.69	
3	156	2.53	
4	88	3.38	
5	56	4.22	

Luminous flux luminaire
764 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable DALI		

Physical

Color	Black/Gold	Length (mm)	147
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.34		

Note

Pre-installation frame not required.

Certification / Marking

