


Light Shadow Fixed Trim Dali Version 8 Spots Optic Medium

03.9142.14ADA - Black/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1813 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 21.6W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 22 |
| Beam angle C90-270 (°) | 22 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 22° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 12201 | 0.39 | |
| 2 | 3050 | 0.77 | |
| 3 | 1356 | 1.16 | |
| 4 | 763 | 1.55 | |
| 5 | 488 | 1.94 | |

Luminous flux luminaire
1813 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | | | |
|----------------------------|--------------|--------------------|-----|
| Color | Black/Chrome | Length (mm) | 287 |
| Orientation | Fixed | | |
| Trim | yes | | |
| Recessed depth (mm) | 75 | | |
| Weight (kg) | 0.50 | | |

Note

Pre-installation frame not required.

