



## Light Shadow Optic Medium Dali Version

03.9622.40ADA - White/Chrome


LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

### Main specifications

|                       |       |                    |                     |
|-----------------------|-------|--------------------|---------------------|
| <b>Lamp category</b>  | LED   | <b>Mountings</b>   | Track               |
| <b>Power (W)</b>      | 10.8W | <b>Environment</b> | Indoor dry location |
| <b>CCT (K)</b>        | 2700K |                    |                     |
| <b>CRI</b>            | 90    |                    |                     |
| <b>Net lumen (lm)</b> | 752   |                    |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Medium    |
| <b>Beam angle (°)</b>         | 22        |
| <b>Beam angle C90-270 (°)</b> | 22        |



Beam Angle: 22°

h(m) E(lx) D(m)

1 5060 0.39

2 1265 0.77

3 562 1.16

4 316 1.55

5 202 1.94

Luminous flux luminaire  
752 lm (EXTREME CUT OFF)

### Electrical

|                    |                 |                         |     |
|--------------------|-----------------|-------------------------|-----|
| <b>Voltage (V)</b> | 24.00           | <b>Insulation class</b> | III |
| <b>Dimmable</b>    | Yes             |                         |     |
| <b>Driver</b>      | Remote excluded |                         |     |
| <b>Driver type</b> | Dimmable DALI 1 |                         |     |
| <b>Emergency</b>   | Without         |                         |     |

### Physical

|                    |              |
|--------------------|--------------|
| <b>Color</b>       | White/Chrome |
| <b>Orientation</b> | Fixed        |
| <b>Weight (kg)</b> | 0.34         |
| <b>Length (mm)</b> | 140          |

### Note

For wireless lighting control, choose integrated Casambi versions.

