



Light Shadow Optic Medium Dali Version

■ 03.9630.14ADA - Black/White


LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Main specifications

| | | | |
|-----------------------|-------|--------------------|---------------------|
| Lamp category | LED | Mountings | Track |
| Power (W) | 10.8W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |
| Net lumen (lm) | 793 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 22 |
| Beam angle C90-270 (°) | 22 |



Beam Angle: 22°

h(m) E(lx) D(m)

1 5302 0.39

2 1325 0.78

3 589 1.17

4 331 1.56

5 212 1.95

Luminous flux luminaire
793 lm (EXTREME CUT OFF)

Electrical

| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable DALI 1 | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|-------------|
| Color | Black/White |
| Orientation | Fixed |
| Weight (kg) | 0.34 |
| Length (mm) | 140 |

Note

For wireless lighting control, choose integrated Casambi versions.

