

## Light Shadow Optic Medium On Board Dimmer

■ ■ 03.9631.40A - White/Black

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.




### Main specifications

Lamp category	LED	Net lumen (lm)	793
Power (W)	10.8W	Mountings	Track
System power (W)	13.4	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22
UGRL	3
Efficiency (lm/W)	59.18



Beam Angle: 22°

h(m) E(lx) D(m)

1 5425 0.39

2 1356 0.78

3 603 1.17

4 339 1.56

5 217 1.95

Luminous flux luminaire  
793 lm (EXTREME CUT OFF)

### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmer on board		
Emergency	Without		

### Physical

Color	White/Black
Orientation	Fixed
Weight (kg)	0.34
Length (mm)	140
Lifespan (L70 B10)	L80B50

### Note

For wireless lighting control, choose integrated Casambi versions.

