

## Light Shadow Optic Spot Casambi integrated

New

## 03.8949.40ACB - White/Black

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.




## Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Lamp category    | LED   | Net lumen (lm) | 724                 |
| Power (W)        | 10.8W | Mountings      | Track               |
| System power (W) | 13.4  | Environment    | Indoor dry location |
| CCT (K)          | 2700K |                |                     |
| CRI              | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 10        |
| Beam angle C90-270 (°) | 10        |
| UGRL                   | 3         |
| Efficiency (lm/W)      | 54.03     |



Beam Angle: 10°

h(m) E(lx) D(m)

1 13076 0.18

2 3269 0.36

3 1453 0.54

4 817 0.72

5 523 0.90

Luminous flux luminaire  
724 lm (EXTREME CUT OFF)

## Electrical

|             |                  |                  |     |
|-------------|------------------|------------------|-----|
| Voltage (V) | 24.00            | Insulation class | III |
| Dimmable    | Yes              |                  |     |
| Driver      | Remote excluded  |                  |     |
| Driver type | Dimmable Casambi |                  |     |
| Emergency   | Without          |                  |     |

## Physical

|                    |             |
|--------------------|-------------|
| Color              | White/Black |
| Orientation        | Fixed       |
| Weight (kg)        | 0.34        |
| Length (mm)        | 140         |
| Lifespan (L70 B10) | L80B50      |

## Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

