

Light Shadow Optic Spot Casambi integrated

New

03.8954.40ACB - White/Chrome

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.




Main specifications

| | | | |
|-----------------------|-------|--------------------|---------------------|
| Lamp category | LED | Mountings | Track |
| Power (W) | 10.8W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |
| Net lumen (lm) | 805 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 10 |
| Beam angle C90-270 (°) | 10 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 10° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 14176 | 0.18 | |
| 2 | 3544 | 0.36 | |
| 3 | 1575 | 0.55 | |
| 4 | 886 | 0.73 | |
| 5 | 567 | 0.91 | |

Luminous flux luminaire
805 lm (EXTREME CUT OFF)

Electrical

| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable | | |
| Emergency | Casambi | | |
| | Without | | |

Physical

| | |
|--------------------|--------------|
| Color | White/Chrome |
| Orientation | Fixed |
| Weight (kg) | 0.34 |
| Length (mm) | 140 |

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

