



## Light Shadow Optic Wide Flood On Board Dimmer

03.9665.14A - Black/Black


LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

### Main specifications

Lamp category	LED	Net lumen (lm)	784
Power (W)	10.8W	Mountings	Track
System power (W)	13.4	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	47
Beam angle C90-270 (°)	47
UGRL	8
Efficiency (lm/W)	58.51



Beam Angle: 46°

h(m) E(lx) D(m)

1 1488 0.84

2 372 1.69

3 165 2.53

4 93 3.38

5 60 4.22

Luminous flux luminaire  
784 lm (EXTREME CUT OFF)

### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmer on board		
Emergency	Without		

### Physical

Color	Black/Black
Orientation	Fixed
Weight (kg)	0.34
Length (mm)	140
Lifespan (L70 B10)	L80B50

### Note

For wireless lighting control, choose integrated Casambi versions.

