


## Light Shadow Pro Ø 60 Fixed Optic Medium

New

## 03.9911.06 - Chrome

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1327                |
| Lamp category   | LED   | Mountings      | Recessed            |
| Power (W)       | 15W   | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 25        |
| Beam angle C90-270 (°) | 25        |



Beam Angle: 25°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 7851 | 0.45  |      |
| 2 | 1963 | 0.89  |      |
| 3 | 872  | 1.34  |      |
| 4 | 491  | 1.78  |      |
| 5 | 314  | 2.23  |      |

Luminous flux luminaire  
1345 lm

## Electrical

|              |                                                                                                               |                  |     |
|--------------|---------------------------------------------------------------------------------------------------------------|------------------|-----|
| Current (mA) | 400                                                                                                           | Insulation class | III |
| Dimmable     | Yes                                                                                                           |                  |     |
| Driver       | Remote excluded                                                                                               |                  |     |
| Driver type  | Non Dimmable, Dimmable DALI 2, Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                  |     |
| Emergency    | Without                                                                                                       |                  |     |

## Physical

|                     |        |
|---------------------|--------|
| Color               | Chrome |
| Orientation         | Fixed  |
| Recessed depth (mm) | 91     |
| Weight (kg)         | 0.22   |
| Spot diameter (mm)  | 60     |

## Note

Please select 300 mA setting in the remote driver to match the power of the Adjustable version.

## Light Shadow Pro Ø 60 Fixed Optic Medium



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W  
60.9186



Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W  
60.9467



Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2  
60.9222



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming  
60.9188



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



Installation Frame Trim  
08.0160.40




---

Installation Frame Trim  
08.0160.14




---

Installation Frame No Trim  
08.0192.00




---

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-36W  
60.9439




---

Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W  
60.9160