


## Light Shadow Pro Ø 60 Fixed Optic Wide Flood

New

03.9913.40 - White

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1316                |
| Lamp category   | LED   | Mountings      | Recessed            |
| Power (W)       | 15W   | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | LED array  |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 51         |
| Beam angle C90-270 (°) | 51         |



Beam Angle: 51°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1767  | 0.95 |
| 2    | 442   | 1.89 |
| 3    | 196   | 2.84 |
| 4    | 110   | 3.79 |
| 5    | 71    | 4.74 |

Luminous flux luminaire  
1316 lm

## Electrical

|              |                                                                                                               |                  |     |
|--------------|---------------------------------------------------------------------------------------------------------------|------------------|-----|
| Current (mA) | 400                                                                                                           | Insulation class | III |
| Dimmable     | Yes                                                                                                           |                  |     |
| Driver       | Remote excluded                                                                                               |                  |     |
| Driver type  | Non Dimmable, Dimmable DALI 2, Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                  |     |
| Emergency    | Without                                                                                                       |                  |     |

## Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Orientation         | Fixed |
| Recessed depth (mm) | 91    |
| Weight (kg)         | 0.22  |
| Spot diameter (mm)  | 60    |

## Note

Please select 300 mA setting in the remote driver to match the power of the Adjustable version.

# Light Shadow Pro Ø 60 Fixed Optic Wide Flood



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming 60.9188

Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2 60.9222

Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W 60.9467



Installation Frame Trim 08.0160.14

Installation Frame No Trim 08.0192.00

Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W 60.9160




---

Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W  
60.9186

---

Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207

---

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-36W  
60.9439




---

Installation Frame Trim  
08.0160.40