

Light Shadow Pro Ø60 Adjustable Optic Spot

03.9971.06 - Chrome




LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

Main specifications

| | | | |
|------------------------|-------|-----------------------|----------|
| Number of heads | 1 | Net lumen (lm) | 672 |
| Lamp category | LED | Mountings | Recessed |
| Power (W) | 10,5W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical


| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 16 |
| Beam angle C90-270 (°) | 16 |



Beam Angle: 16°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 7691 | 0.28 |
| 2 | 1923 | 0.56 |
| 3 | 855 | 0.84 |
| 4 | 481 | 1.12 |
| 5 | 308 | 1.40 |

Luminous flux luminaire
672 lm



Electrical

| | | | |
|---------------------|--|-------------------------|-----|
| Current (mA) | 750 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic, Electronic dimmable 1-10V, Electronic dimmable DALI | | |
| Emergency | Without | | |


Physical

| | | | |
|----------------------------|------------|---------------------------|-----|
| Color | Chrome | Rotation (°) | 355 |
| Orientation | Adjustable | Spot diameter (mm) | 60 |
| Recessed depth (mm) | 93 | | |
| Weight (kg) | 0.22 | | |
| Tilt (°) | 30 | | |

Note

Preliminary photometries.

Certification / Marking



Light Shadow Pro Ø60 Adjustable Optic Spot



Installation Frame Trim
08.0164.40



Installation Frame Trim
08.0164.14



Installation Frame No Trim
08.0166.00