

## Light Shadow Pro Ø60 Fixed Optic Flood

■ 03.9952.06 - Chrome




LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1225
<b>Lamp category</b>	LED	<b>Mountings</b>	Recessed
<b>Power (W)</b>	15W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	34
<b>Beam angle C90-270 (°)</b>	34



Beam Angle: 34°

h(m)	E(lx)	D(m)
1	4060	0.61
2	1015	1.22
3	451	1.82
4	254	2.43
5	162	3.04

Luminous flux luminaire  
1225 lm




### Electrical

<b>Current (mA)</b>	400	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable 1-10V, Electronic dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Chrome
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	91
<b>Weight (kg)</b>	0.22
<b>Spot diameter (mm)</b>	60



# Light Shadow Pro Ø60 Fixed Optic Flood



Installation Frame Trim  
08.0160.40

Installation Frame Trim  
08.0160.14

Installation Frame No Trim  
08.0162.00



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200mA – 8,5W / 250mA – 11W / 300mA – 13W / 350mA – 15W / 400mA – 17,5W / 450mA 19,5W / 500mA – 22W.  
60.9160

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 36W – 700 mA  
60.9439

Continuous current supply source of 240V – 50/60Hz with dimmable DALI 2  
60.9186



Continuous current power supply of

Continuous current power supply of

Continuous current power supply of

switch  
60.9162



adjustable switch. 1-10V or push  
dimming.  
60.9188



adjustable. Regulable DALI 1 y DALI 2  
60.9222

---

Continuous current power supply,  
Mains dimming 220/240V – 50/60Hz, 12-  
20W  
60.9467

---

Continuous current power supply,  
dimmable Casambi, 220/240V –  
50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207