


## Light Shadow Pro Ø60 Fixed Optic Wide Flood

■ 03.9957.14 - Black

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1199
<b>Lamp category</b>	LED	<b>Mountings</b>	Recessed
<b>Power (W)</b>	15W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	49
<b>Beam angle C90-270 (°)</b>	49



Beam Angle: 49°		
h(m)	E(lx)	D(m)
1	1759	0.91
2	440	1.82
3	195	2.73
4	110	3.64
5	70	4.55

Luminous flux luminaire  
1199 lm

### Electrical

<b>Current (mA)</b>	400	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmmable 1- 10V, Electronic dimmmable DALI		
<b>Emergency</b>	Without		


### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	91
<b>Weight (kg)</b>	0.22
<b>Spot diameter (mm)</b>	60

### Note

Preliminary photometries.

### Certification / Marking



## Light Shadow Pro Ø60 Fixed Optic Wide Flood



---

Installation Frame Trim  
08.0160.40



---

Installation Frame Trim  
08.0160.14



---

Installation Frame No Trim  
08.0162.00