

## Light Shadow Pro Ø90 Fixed Optic Spot

■ 03.9964.14 - Black

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.


LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2032
<b>Lamp category</b>	LED	<b>Mountings</b>	Recessed
<b>Power (W)</b>	22W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	13
<b>Beam angle C90-270 (°)</b>	13



<b>Beam Angle:</b>	13°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	32734	0.23	
2	8183	0.45	
3	3637	0.68	
4	2046	0.91	
5	1309	1.13	

Luminous flux luminaire  
2032 lm

### Electrical

<b>Current (mA)</b>	600	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable 1- 10V, Electronic dimmable DALI		
<b>Emergency</b>	Without		


### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	129
<b>Weight (kg)</b>	0.54
<b>Spot diameter (mm)</b>	90

### Note

Preliminary photometries.

### Certification / Marking



## Light Shadow Pro Ø90 Fixed Optic Spot



---

Installation Frame Trim  
08.0161.40



---

Installation Frame Trim  
08.0161.14



---

Installation Frame No Trim  
08.0193.00