


## Light Shadow Surface 4 Spots Optic Wide Flood

03.9866.40A - Black/White/Chrome

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 789                 |
| Lamp category   | LED   | Mountings      | Surface             |
| Power (W)       | 10.8W | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Power LED  |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 44         |
| Beam angle C90-270 (°) | 44         |



Beam Angle: 44°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1644  | 0.80 |
| 2    | 411   | 1.60 |
| 3    | 183   | 2.40 |
| 4    | 103   | 3.19 |
| 5    | 66    | 3.99 |

Luminous flux luminaire  
789 lm (EXTREME CUT OFF)

### Electrical

|                |              |                  |         |
|----------------|--------------|------------------|---------|
| Frequency (Hz) | 50/60        | Emergency        | Without |
| Voltage (V)    | 220.00       | Insulation class | I       |
| Dimmable       | No           |                  |         |
| Driver         | Integrated   |                  |         |
| Driver type    | Non Dimmable |                  |         |

### Physical

|             |                    |
|-------------|--------------------|
| Color       | Black/White/Chrome |
| Orientation | Fixed              |
| Weight (kg) | 0.80               |
| Length (mm) | 146                |

