



## Light Shadow Wall-Washer DALI Version

■ 03.9904.14BDA - Black


LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

### Main specifications

Lamp category	LED	Net lumen (lm)	696
Power (W)	10.8W	Mountings	Track
System power (W)	13.4	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wall Washer
	Down
Beam angle (°)	23
Beam angle C90-270 (°)	46
Efficiency (lm/W)	51.94



Beam Angle: 22°

h(m) E(lx) D(m)

1 77 80.03

2 19 160.07

3 8 240.10

4 5 320.13

5 3 400.17

Luminous flux luminaire  
696 lm

### Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
	2		
Emergency	Without		

### Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.34
Length (mm)	140
Lifespan (L70 B10)	L80B50

### Note

For wireless lighting control, choose integrated Casambi versions.

