



Light Shadow Wall Washer No Trim 4 Spots

■ 03.9902.14A - Black

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	730
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Asymmetric Wall Washer
Optical type	Down
Beam angle (°)	23
Beam angle C90-270 (°)	46



Beam Angle:	23°		
h(m)	E(lx)	D(m)	
1	967	0.48	
2	242	0.97	
3	107	1.45	
4	60	1.94	
5	39	2.42	

Luminous flux luminaire
730 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		


Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

Note

It requires a pre-installation frame, to be ordered separately (08.0511.00)

Light Shadow Wall Washer No Trim 4 Spots



Pre-installation Frame
08.0511.00

Accessory for mounting of No Trim
continuous line.
08.0052.90