


■ 03.9902.14ADA - Black

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).









11/	าวเก	specifications
10	ıaııı	SUCCINCATIONS

Number of heads LED Lamp category Power (W) 10.8W CCT (K) 3000K CRI 90


Net lumen (lm) Mountings Environment

730

Ceiling recessed Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Asymmetric Optical type Wall Washer Down Beam angle (°) 23 Beam angle C90-270 (°) 46



Beam	23°	
h(m)	E(l x)	D(m)
1	967	0.48
2	242	0.97
3	107	1.45
4	60	1.94
5	39	2.42

Luminous flux luminaire (EXTREME CUT OFF)

Electrical

Frequency (Hz) 50/60 **Emergency** Without Voltage (V) 220.00 Insulation class Dimmable Yes Driver Remote included

Dimmable DALI

Physical

Driver type

Color Black Orientation Fixed Recessed depth (mm) 75 Weight (kg) 0.34 Length (mm) 140

Note

It requires a pre-installation frame, to be ordered separately (08.0511.00)

1

Light Shadow Wall Washer No Trim Dali Version 4 Spots





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90