


03.9902.40ADA - White

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).














Number of heads LED Lamp category Power (W) 10.8W CCT (K) 3000K CRI 90


Net lumen (lm) Mountings Environment

730

Ceiling recessed Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Asymmetric Wall Washer Optical type Down Beam angle (°) 23 Beam angle C90-270 (°) 46



Luminous flux luminaire (EXTREME CUT OFF)

Beam Angle:		23°
h(m)	E(l ×)	D(m)
1	967	0.48
2	242	0.97
3	107	1.45
4	60	1.94
5	39	2 42

Electrical

Frequency (Hz) 50/60 **Emergency** Without Voltage (V) 220.00 Insulation class Dimmable Yes Driver Remote included

Dimmable DALI

Physical

Driver type

Color White Orientation Fixed Recessed depth (mm) 75 Weight (kg) 0.34 Length (mm) 140

Note

It requires a pre-installation frame, to be ordered separately (08.0511.00)

1

Light Shadow Wall Washer No Trim Dali Version 4 Spots





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0511.00