




03.9900.40A - White

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).









| 11\/1 | ain | cno | CITIC | ations |
|-------|-------|------|-------|-----------|
| 101 | alli | שנום | | 211112112 |
| | ••••• | | • | |
| | | | | |

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 10.8W

 CCT (K)
 3000K


 CRI
 90

Net lumen (lm) Mountings Environment 730 Ceilin

Ceiling recessed Indoor dry location

Optical

Lighting type Direct
LED type Power LED
Light distribution Asymmetric
Optical type Wall Washer
Down
Beam angle (°) 23
Beam angle C90-270 (°) 46



Beam Angle: 23° E(lx) h(m) D(m) 967 0.48 2 242 0.97 3 107 1.45 4 60 1.94 5 39 2.42

Luminous flux luminaire 730 lm (EXTREME CUT OFF)

Electrical

 Frequency (Hz)
 50/60

 Voltage (V)
 220.00

 Dimmable
 No

 Private
 Remote

Driver Remote included Emergency Without

Physical

 Color
 White

 Orientation
 Fixed

 Trim
 yes

 Recessed depth (mm)
 75

 Weight (kg)
 0.34

Length (mm) 148

Insulation class

Note

Pre-installation frame not required.