

Light Shooter Adjustable No Trim

■ 03.6520.14A - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	328
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle: 13°		
h(m)	E(lx)	D(m)
1	4026	0.22
2	1006	0.44
3	447	0.66
4	252	0.88
5	161	1.10

Luminous flux luminaire
328 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	12.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	170		
Weight (kg)	0.45		
Tilt (°)	40		

Note

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.



Light Shooter Adjustable No Trim



Honeycomb
08.8412.14



Elliptical light distribution lens
08.8041.68