


## Light Shooter Adjustable No Trim

03.6520.40A - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




### Main specifications

Number of heads	1	Net lumen (lm)	328
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle: 13°

h(m)	E(lx)	D(m)
1	4026	0.22
2	1006	0.44
3	447	0.66
4	252	0.88
5	161	1.10

Luminous flux luminaire  
328 lm (EXTREME CUT OFF)

### Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	12.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

### Physical

Color	White	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	170		
Weight (kg)	0.45		
Tilt (°)	40		

### Note

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.



## Light Shooter Adjustable No Trim



---

Elliptical light distribution lens  
08.8041.68



---

Honeycomb  
08.8412.14